



# AMPLIN GEN2

## LINEAR HIGH BAY

(POWER SELECTABLE)

IKIO's Amplin Gen2 Linear High Bay comes with power selectable capability, making it perfect for a variety of applications. With features like wide-angle optics, a robust heat sink, surge protection, and high luminance, Amplin Gen2 not only offers long-lasting performance, but also ensures greater savings than traditional linear fixtures. Suggested mounting heights are between 15 and 25 feet. The luminaire is also easy to set up, resulting in a seamless lighting upgrade experience.

**Applications:** Ideal for Industrial Applications—Manufacturing Facilities, Warehouses, Gymnasiums, Athletic Facilities, Workshops, Large Areas, Parking Lots

## FEATURES

- **Sleek, low-profile design and power selectable feature** make it suitable for a wide range of applications.
- **Superior heat dissipation capability** due to an efficient heat sink, complemented by a strong aluminum exterior.
- **Exceptional efficacy and high CRI** ensure great visibility and true-to-life visual experience.
- **75,000 hours of smooth and uniform light output** without any flickering.
- **In-built surge protection** helps keep the voltage in check.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



## PRODUCT ORDERING DETAILS

### AMPLIN GEN2 LINEAR HIGH BAY- 100-277 V

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	SPEC SHEET
662187487656	AMPLIN GEN2 LHB: 100-150-200 W / 14805-21905-28193 LM / 5000 K / 100-277 V / WHITE		148.16 lm/W	<a href="#">View / Download</a>
662187487571	AMPLIN GEN2 LHB: 200-240-300 W / 28193-35532-44101 LM / 5000 K / 100-277 V / WHITE		148.16 lm/W	<a href="#">View / Download</a>

## ACCESSORIES

### INCLUDED IN THE BOX

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187476049	IK-ACC-ARC	SUSPENSION CABLE KIT	<a href="#">View / Download</a>

### SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187557700	IK-OCCS-B	IK-OCCS-B: HD406VRH-D: Microwave Smart Controller (Black Sensor)	<a href="#">View / Download</a>
662187558097	IK-OCCS-W	IK-OCCS-W: HD406VRH-D: Microwave Smart Controller (White Sensor)	<a href="#">View / Download</a>
662187487854	IK-ACC-HD05R-Digital	MICROWAVE MOTION SENSOR REMOTE	<a href="#">View / Download</a>
662187479033	IK-EMH-18170-HY	EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L (ON FIELD)	<a href="#">View / Download</a>
662187558875	IK-10W-ED	EMERGENCY PACK FOR LED FIXTURE 10W/90 MIN/SPLIT TYPE/L (FACTORY INSTALLED)	<a href="#">View / Download</a>
662187486444	IK-ACC-HD07VR	IK-ACC-HD07VR 3 Pin Microwave Motion Sensor	<a href="#">View / Download</a>

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.