Product Sheet















Not all product variations listed on this page are DLC qualified. Visit https://www.designlights.org/qp. to confirm qualification.

IKIO's Apex Linear Low Bay comes with CCT and power selectable capability, making it not only an energy-efficient alternative to traditional lights but also a high-performance lighting solution with better control. Given the flexibility, you can choose this luminaire for a variety of lighting applications while using lesser number of SKUs. Apex is easy to install and has features like high light output, smooth color rendering, dimming options, and even distribution.

Applications: Parking Lots, Garages, Warehouses, Workshops & Production Areas, Walkways, Restaurants, Retail Stores

FEATURES

- Increased flexibility and ease with IKIO's CCT Selectable & Power Selectable feature.
 - **High Efficacy Lighting with 80+ CRI,** resulting in crisp, uniform, and flicker-free illumination of the space.
 - Easy-to-install Design that supports Quick Screw-in during lighting installations, making upgrades hassle-free.
- **Ensured longevity** with rugged iron housing, an effective heat sink, and durable polycarbonate lens.
- 0-10 V Seamless Dimming function, allowing adjustment of the brightness of lights.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

APEX LINEAR LOW BAY - WITH SENSOR

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187482798	APEX LLB: 72.4 W / 6993.5-8392.2-10123 LM / 30-40-50 K / 120-277 V / WHITE / WITH SENSOR	•	139.87 lm/W	300 W	View / Download

APEX LINEAR LOW BAY - WITHOUT SENSOR

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187482781	APEX LLB: 72.4 W / 6993.5-8392.2-10123 LM / 30-40-50 K / 120-277 V / WHITE / WITHOUT SENSOR	•	139.87 lm/W	300 W	View / Download

ACCESSORIES

INCLUDED IN THE BOX (WITH SENSOR)

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187478845	IK-HD016VCR	MICROWAVE MOTION SENSOR	View / Download
662187477046	IK-ACC-HD05R	REMOTE FOR MICROWAVE MOTION SENSOR	View / Download
662187482828	IK-LLB08-SMK	SURFACE MOUNT KIT	View / Download

INCLUDED IN THE BOX (WITHOUT SENSOR)

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187482828	IK-LLB08-SMK	SURFACE MOUNT KIT	View / Download

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187482811	IK-LLB-LP	LINKABLE PLATE	View / Download
662187482842	IK-LLB08-ARC	SUSPENSION CABLE KIT	View / Download
662187482835	IK-ACC-8W-EMD	EMERGENCY LED DRIVER	View / Download

NOTE: Surface mounting kit is inside the fixture.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

