

Product Specification Sheet | Industrial Lighting

NOTES :
PROJECT NAME :
CATALOG NO. :
FIXTURE SCHEDULE :



Augustus Wall Pack Light (Full Cutoff)

FEATURES

- Saves up to 50% energy as compared to traditional lighting fixtures.
- Exceptional light output with even and wide distribution.
- · Quick and easy installation.
- Can be used to replace HIDs up to 400 W.
- Rugged construction with sealed die-cast profile makes it ideal for outdoor applications.
- Alkali and salt erosion resistant.
- Suitable for operation in low working temperature.

PRODUCT DETAILS

LIGHTING PERFORMANCE			
Efficacy	100 lm/W		
Power	80 W	100 W	
Lumen Output	8000 lm	10000 lm	
ССТ	3000 K, 3500 K, 4000 K, 4500 K, 5000 K		
CRI	80+		
Voltage	AC 100-2	77 V 50/60 Hz	
Beam Angle	-		
Power factor	≥ 0.90		
Dimming	No		

END/	IDON	BALLIT	0 1	IEECDAN
ENV	IKUN	MENI	& L	IFESPAN

Operating Temperature	-20° F to +140° F
IP Rating	IP65
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years / 10 Years (Optional)

CONSTRUCTION

Housing	Die Cast Aluminum	
Base / Power Supply	Hard Wired	
Finish	Bronze / Black	

APPLICATIONS

Security, Landscape, Accent Lighting, Signage, and Façade Applications

QUALIFICATIONS & WARRANTY











DIMENSIONS

Wattage	A(in)	B(in)	C(in)
80 W / 100	W 10.07	4.40	14.25





ORDERING INFORMATION

MODEL	POWER	сст
IKPCWP	- 80W	- (3000K)
	100W	(3000K)
		(3500K)
		(4000K)
		(4500K)
		(5000K)



Product Specification Sheet | Industrial Lighting

PACKAGING

Quantity Per Box	1
Box Dimensions	
Box Weight	

ACCESSORIES/REPLACEMENT PARTS

BUTTON STYLE PHOTO CELL FOR LED WALL PACK - SERIES 5/120-277V

REPLACEMENT LENS FOR LED WALL PACK - SERIES 5

80W/100W REPLACEMENT DRIVER

OPTOMETRIC DATA

