

Product Specification Sheet | Commercial Lighting

NOTES:	
PROJECT NAME :	
CATALOG NO. :	
FIXTURE SCHEDULE :	



Contrila CCT & Power Tunable Edge-lit Panel Light 2' x 4'

FEATURES

- Edge-lit low-profile design.
- CCT and wattage tunable for enhanced light control.
- High-quality LGP for evenly distributed light.
- Supports 0-10 V dimming.

PRODUCT DETAILS

LIGHTING PERFORMANCE			
Efficacy	125 lm/W		
Power	35 W / 40 W / 45 W / 50 W		
Lumen Output	4375 lm / 5000 lm / 5625 lm / 6250 lm		
Tunable CCTs	3000 K / 3500 K / 4000 K / 5000 K		
CRI	80+		
Voltage	AC 120 - 277 V / AC 50 / 60 Hz or AC 120 - 347 V		
Beam Angle	120°		
Power factor	> 0.90		
Dimming	Yes		
ENVIRONMENT & LIFESPAN			

Operating Temperature	-4° F to +113° F
Rating	IP40
Operating Hours	Over 50,000 hours lifetime at L70
Warrantv	5 Years / 10 Years (Optional)

CONSTRUCTION

Housing	Aluminum+ High Quality LGP			
Base / Power Supply	Hard Wired			
Finish	White			

APPLICATIONS

Ideal for retrofitting inefficient light fixtures in malls, hospitals, airports, offices, lobbies and other commercial applications.

QUALIFICATIONS, WARRANTY
















DIMENSIONS

Wattage	A(in)	B(in)	C(in)	D(in)	
35 W - 50 W	17 75	45 08	23.74	21.06	



ORDERING INFORMATION

MODEL		POWER		DIMMING		CCT
IK-FP24] -	0050	-	DY	-	XX-J
				DY - Dimmable		XX - Tunable



Product Specification Sheet | Commercial Lighting

PACKAGING

Quantity Per Box	
Box Dimensions	
Box Weight	

ACCESSORIES

SURFACE MOUNTING KITS

FLANGE KIT

SUSPENDED CABLE MOUNTING KITS

EMERGENCY PACK FOR LED FIXTURE 10 W / 90 MIN

EMERGENCY PACK FOR LED FIXTURE 15 W / 90 MIN

40 W REPLACEMENT LED POWER SUPPLY

TUNING FUNCTIONS

