



Not all product variations listed on this page are DLC qualified. Visit <https://www.designlights.org/qpl> to confirm qualification.

DELPHI

ARCHITECTURAL TROFFER

(CCT & POWER SELECTABLE)

Delphi Architectural Troffer, apart from being an energy efficient lighting solution, also offers excellent lighting control to its users by allowing them to select different CCTs and Power to meet their varied requirements. This Troffer is available in two different sizes (1' x 4', 2' x 2', 2' x 4'), each with a variety of highly efficient lumen packages to suit multiple lighting needs.

Applications : Ideal for large warehouses, retail applications, commercial buildings and work areas.

FEATURES

- **CCT & power selectable** capabilities.
- **Soft, smooth** and uniform light output.
- **Suitable for a wide range** of applications due to its low profile.
- **Metal surfaces are painted pre-fabrication** with high gloss baked silver matte powder paint for a long-lasting finish.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

DELPHI ARCHITECTURAL TROFFER - 1' X 4' - 0-10 V DIMMING

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187488882	DELPHI AT 1' X 4' : 20-25-30 W / 2760-3200-3900 LM / 35-40-50 K / 120-277 V / WHITE	•	128 lm/W	150 W	View / Download

DELPHI ARCHITECTURAL TROFFER - 2' X 2' - 0-10 V DIMMING

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187477305	DELPHI AT 2' X 2' : 20-25-30 W / 2700-3200-3900 LM / 35-40-50 K / 120-277 V / WHITE	•	128 lm/W	150 W	View / Download

DELPHI ARCHITECTURAL TROFFER - 2' X 4' - 0-10 V DIMMING

SKU NUMBER	DESCRIPTION	DLC	EFFICACY	TRAD. EQUIV	SPEC SHEET
662187477312	DELPHI AT 2' X 4' : 25-30-35 W / 3350-3840-4500 LM / 35-40-50 K / 120-277 V / WHITE	•	128 lm/W	175 W	View / Download

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187482651	IK-ACC-R-RC100	RC100 REMOTE	View / Download
662187479033	IK-EMH-18170-HY	EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L DC	View / Download
662187482682	IK-ACC-S-ANT9	BI LEVEL DAYLIGHT HARVESTING MICROWAVE MOTION SENSOR	View / Download
662187487137	IK-ACC-AT-SMKT-14	SURFACE MOUNT KIT 1'x4'	View / Download
662187477091	IK-ACC-AT-SMKT-22	SURFACE MOUNT KIT 2'x2'	View / Download
662187477084	IK-ACC-AT-SMKT-24	SURFACE MOUNT KIT 2'x4'	View / Download
662187481821	IK-ACC-14-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download
662187485850	IK-ACC-22-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download
662187481838	IK-ACC-24-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.