



DELPHI

RETROFIT TROFFER

(CCT & POWER SELECTABLE)

IKIO's Delphi Retrofit Troffer is an energy-efficient alternative to traditional lighting fixtures, offering unparalleled lighting control alongside with its CCT & power selectable capability. The luminaire allows you to select different CCTs and wattages to meet your specific application requirements. In addition, Delphi is available in two different sizes (2' x 2', 2' x 4'), each with various highly efficient lumen packages to cater to your lighting needs better!

Application : Offices, Hallways, Multipurpose Rooms, Conference Rooms

FEATURES

- **CCT & power selectable** capabilities for greater light control.
- **Suitable for damp** locations.
- **Greater energy savings** over traditional fluorescent fixtures.
- **High-gloss finish** for metal surfaces.
- Baked with powder paint for **durability and better aesthetics**.
- **Soft, smooth, and uniform light output**.
- **Can be used with existing fixtures** for retrofit applications.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification.
• Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

DELPHI RETROFIT TROFFER - 1' X 4' - 0-10 V DIMMING

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DLC	EFFICACY	SPEC SHEET
662187484259	IK-RT14F-202530-CCT-D	DELPHI RT 1' x 4' : 20-25-30 W / 2660-3175-3870 LM / 35-40-50 K / 120-277 V / WHITE ONLY FIXTURE / WITHOUT ACCESSORIES	●	127 lm/W	View / Download
662187485775	IK-RT14F-202530-CCT-D-e	DELPHI RT 1' x 4' : 20-25-30 W / 2660-3175-3870 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER	●	127 lm/W	
662187485812	IK-RT14F-202530-CCT-D-s	DELPHI RT 1' x 4' : 20-25-30 W / 2660-3175-3870 LM / 35-40-50 K / 120-277 V / WHITE WITH LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	127 lm/W	
662187485744	IK-RT14F-202530-CCT-D-es	DELPHI RT 1' x 4' : 20-25-30 W / 2660-3175-3870 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER & LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	127 lm/W	

DELPHI RETROFIT TROFFER - 2' X 2' - 0-10 V DIMMING

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DLC	EFFICACY	SPEC SHEET
662187484266	IK-RT22F-202530-CCT-D	DELPHI RT 2' x 2' : 20-25-30 W / 2600-3100-3720 LM / 35-40-50 K / 120-277 V / WHITE ONLY FIXTURE / WITHOUT ACCESSORIES	●	124 lm/W	View / Download
662187485799	IK-RT22F-202530-CCT-D-e	DELPHI RT 2' x 2' : 20-25-30 W / 2600-3100-3720 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER	●	124 lm/W	
662187485829	IK-RT22F-202530-CCT-D-s	DELPHI RT 2' x 2' : 20-25-30 W / 2600-3100-3720 LM / 35-40-50 K / 120-277 V / WHITE WITH LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	124 lm/W	
662187485751	IK-RT22F-202530-CCT-D-es	DELPHI RT 2' x 2' : 20-25-30 W / 2600-3100-3720 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER & LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	124 lm/W	

DELPHI RETROFIT TROFFER - 2' X 4' - 0-10 V DIMMING

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DLC	EFFICACY	SPEC SHEET
662187484273	IK-RT24F-253035-CCT-D	DELPHI RT 2' x 4' : 25-30-35 W / 3400-3840-4480 LM / 35-40-50 K / 120-277 V / WHITE ONLY FIXTURE / WITHOUT ACCESSORIES	●	128 lm/W	View / Download
662187485805	IK-RT24F-253035-CCT-D-e	DELPHI RT 2' x 4' : 25-30-35 W / 3400-3840-4480 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER	●	128 lm/W	
662187485836	IK-RT24F-253035-CCT-D-s	DELPHI RT 2' x 4' : 25-30-35 W / 3400-3840-4480 LM / 35-40-50 K / 120-277 V / WHITE WITH LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	128 lm/W	
662187485768	IK-RT24F-253035-CCT-D-es	DELPHI RT 2' x 4' : 25-30-35 W / 3400-3840-4480 LM / 35-40-50 K / 120-277 V / WHITE WITH EMERGENCY DRIVER & LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	●	128 lm/W	

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187558257	IK-FP14-SMT KIT	SURFACE MOUNT KIT	View / Download
662187559032	IK-FP22-SMT KIT	SURFACE MOUNT KIT	View / Download
662187558295	IK-FP24-SMT KIT	SURFACE MOUNT KIT	View / Download

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	DOCUMENT LINK
662187485843	IK-ACC-S-ANT9C	LOW VOLTAGE MICROWAVE BI-LEVEL SENSOR	View / Download
662187481821	IK-ACC-14-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download
662187485850	IK-ACC-22-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download
662187481838	IK-ACC-24-FLMK	FLANGE/DRYWALL MOUNT KIT	View / Download
662187485867	IK-ACC-R-RC106	REMOTE	View / Download
662187479033	IK-EMH-18170-HY	EMERGENCY PACK FOR LED FIXTURE 18W/90 MIN/SPLIT TYPE/L	View / Download

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.