Y		GHTING		
Produ	ıct S	pecific	cation	Sheet

OTES:
ROJECT NAME :
ATALOG NO. :
XTURE SCHEDULE :



Discuz Round Panel Ceiling Light

FEATURES

- Superior efficacy over traditional light fixtures.
- Built to function in damp locations as well.
- White Acrylic Diffuser for an evenly distributed light.
- Comes with 120V Triac Dimmable Drivers for enhanced light control.
- 80+ and 90+ CRI light variants for crisp colors.

PRODUCT DETAILS

LIGHTING PERFORMANCE							
Efficacy	80 lm/W						
Power	12 W	20 W					
Lumen Output	Dutput 960 lm 1200 lm 1600 lm						
ССТ	3000 K, 4000 K, 5000 K						
CRI	80+/90+						
Voltage	120 V-277 V, 50 Hz / 60 Hz						
Power factor	≥ 0.90						
Dimming	Yes, with remote control (optional)						

CONSTRUCTION						
Finish	White / Black / Brushed Nickel					
Material	Metal					
Lens	Acrylic Lens					
A DDI IO ATIONO						

APPLICATIONS

Damp Location

ENVIRONMENT & LIFESPAN

IP Rating	IP 42
Operating Hours	50,000 hours
Warranty	5 Years

QUALIFICATIONS & WARRANTY







Wattage	A(in)	B(in)	
12 W - 20 W	9 / 11 / 13	1.125	



ORDERING INFORMATION

MODEL		DIMENSIONS		WATTAGE		CRI & CCT		DRIVER		FINISH
IK-FPCL	-	9	-	12WS] -	80C3K	-	120VDY	-	WH
		9		12WS	•	80C3K 90C4K		120VDY		WH-White
		11		15WS		80C4K 90C5K				BK- Black
		13		20WS		80C5K				BN- Brushed Nickel
						90C3K				