

Frizo Refrigeration Light (5 ft)

FEATURES

- Fog and Corrosion resistant.
- Ideal to be used inside refrigerators and coolers at commercial establishments.
- Up to 10 lamps can be connected in a series.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	115 lm/W	130 lm/W
Power	20 W	22 W
Lumen Output	2300 lm	2860 lm
CCT	3000 K, 3500 K, 4000 K, 5000 K	
CRI	80+	
Voltage	AC 100-277 V 50/60 Hz	
Beam Angle	120°	
Power factor	≥ 0.90	
Dimming	No	

ENVIRONMENT & LIFESPAN

Operating Temperature	-4° F to +140° F
IP Rating	IP66
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	Hard Wired
Finish	White

APPLICATIONS


Refrigeration Area & Cold Storages

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
20 W / 22 W	60	1	1



ORDERING INFORMATION

MODEL	POWER	CCT
IK-RL05IN	0020 0022	30-J 30- 3000K 35- 3500K 40- 4000K 50- 5000K

PACKAGING


Quantity Per Box	20
Box Dimensions	-----
Box Weight	-----

ACCESSORIES / REPLACEMENT PARTS

METAL BRACKET (SET OF 2)
SPLITTER CABLE (TO CONNECT UPTO 10 COOLER LIGHTS IN SERIES)
SINGLE OUTPUT WIRE

OPTOMETRIC DATA

20 W



22 W

