

LANTORCH

Drop Light



DROP LIGHT CLASS I DIVISION 2

Product Description:

Lantorch Drop light is a special lamp with the ability to operate in rough environmental conditions. Designed for use in hazardous locations, this luminaire has a heavily sealed lamp enclosure & guards to prevent the lamp from breaking. The sturdy lamp shield along with the durable aluminum housing ensures longer lifespan of the luminaire.

Classifications / Ratings

- **Class I, Division 2, Groups A, B, C, D**
- **Class II, Division 1&2, Groups F, G**
- **Marking UL844 (North American)**
- **Class III**

Environmental

- Ambient Operating Temperature -40 °F ~ +122°F
- Ingress Protection Rating of **IP67**
- Average Life of 50000 Hours.

Construction


Housing	Copper-free aluminum
Cover Material / Lens	Glass

Application Areas

- Oil and gas industry
- Chemical industry
- Marine and aerospace field
- Metal treatment
- Food and alcohol industry



Dimension Diagram



Warranty

- 5-year limited system warranty standard
- Warranty does not cover product failure due to an overvoltage event (power surge)

Product Specifications:

Item	Specification	Details	
Model Version		LL130 (Lantorch)	
Electrical	Power	20W	30W
	Voltage	100-277 V AC 50/60 Hz	
Lighting Performance	Lumens	2000 lm	3000 lm
	Efficacy	100 lm/W	

Ordering Information : Typical order example: IK-EXHB-LL130-20W-40K-CID2

IK	EXHB	LL130			CID2
BRAND	FAMILY	MODEL	POWER	CCT	CLASSIFICATION
IK IKIO	EXHB Explosion Proof High Bays	LL130 Lantorch Drop Light	<input type="checkbox"/> 20W <input type="checkbox"/> 30W	<input type="checkbox"/> 40K for 4000K <input type="checkbox"/> 50K for 5000K	CID2 CID2 Explosion Proof Rated

Mounting Methods:

