



Lantorch Portable Guarded Trouble Work Light

FEATURES

- Copper-free aluminum body.
- High Efficacy of up to 100 lm/W.
- Rated for marine and wet locations.

PRODUCT DETAILS

LIGHTING PERFORMANCE

| | | | | |
|--------------|--------------------------------|--------|--------|--------|
| Efficacy | 100 lm/W | | | |
| Power | 3 W | 5 W | 7 W | 9 W |
| Lumen Output | 300 lm | 500 lm | 700 lm | 900 lm |
| CCT | 3000 K, 4000 K, 5000 K, 7000 K | | | |
| CRI | 70+ | | | |
| Voltage | AC 100 - 277 V | | | |

ENVIRONMENT & LIFESPAN

| | |
|-----------------------|-------------------------------|
| Operating Temperature | -40° F to +122° F |
| IP Rating | IP66 |
| Operating Hours | Over 50,000 hours |
| Warranty | 5 Years / 10 Years (Optional) |

CONSTRUCTION

| | |
|---------------------|----------------------|
| Housing | Copper-free Aluminum |
| Base / Power Supply | Direct Wire |
| Finish | Metallic Gray |

APPLICATIONS

Manufacturing plants, chemical plants, paint shops, oil refineries, gas stations, industrial facilities, warehouses, processing plants and other Class I, II and III hazardous locations.


QUALIFICATIONS, WARRANTY AND RATINGS

1. Class I, Division 2, Group A, B, C, D
2. Class II, Division 1 & 2, Group E, F, G
3. Class III



DIMENSIONS

| Wattage | A(in) | B(in) |
|-----------|-------|-------|
| 3 W - 9 W | 20.7 | 5.2 |



ORDERING INFORMATION

| MODEL | POWER | CCT |
|---------------|-------|--------------|
| IK-EXSL-LL140 | 003W | 30K |
| | 005W | 30K - 3000 K |
| | 007W | 40K - 4000 K |
| | 009W | 50K - 5000 K |
| | | 70K - 7000 K |