



Lupos Wall Pack Light (Directional)

FEATURES

- Saves upto 50% energy as compared to traditional lighting fixtures.
- Exceptional light output with even and wide distribution.
- Quick and easy installation.
- Can be used to replace HID's up to 75 W.
- Rugged construction with sealed die-cast profile makes it ideal for outdoor applications.
- Alkali and salt erosion resistant.
- Suitable for operation in low working temperature.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	100 lm/W		
Power	30 W	60 W	80 W
Lumen Output	3000 lm	6600 lm	8800 lm
CCT	3000 K, 5000 K, 5700 K		
CRI	80+		
Voltage	AC 100-277 V 50/60 Hz		
Beam Angle	240°		
Power factor	≥ 0.90		
Dimming	No		

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +176° F
IP Rating	-
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years / 10 Years (Optional)

CONSTRUCTION

Housing	Aluminum
Base / Power Supply	Hard Wired
Finish	Bronze

APPLICATIONS


Wall washing, landscaping lighting, outdoor advertising and square nocturnes

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
30 W- 80 W	7.87	6.61	4.33



ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT
IK-WPBO-L110	0030 0060 0080	DN	30-ML 30- 3000K 50- 5000K 57- 5700K

PACKAGING

Quantity Per Box	-----
Box Dimensions	-----
Box Weight	-----

ACCESSORIES / REPLACEMENT PARTS

IK83712	U SHAPED MOUNTING BRACKET FOR UNIVERSAL WALL PACK - SUPERIOR LIFE®
IK83713	SWIVEL FOR 1/2" MOUNTING FOR UNIVERSAL WALL PACK - SUPERIOR LIFE®
IK83714	PHOTO CELL FOR UNIVERSAL WALL PACK - SUPERIOR LIFE®

1.PHOTOCELL: IK-PCWPS3



OPTOMETRIC DATA

