

Product Specification Sheet | Industrial Lighting

NOTES:	
PROJECT NAME :	
CATALOG NO. :	
FIXTURE SCHEDULE :	





Ortega Fuel Pump Canopy Light

FEATURES

- Upto 75% savings in energy consumption and maintenance cost.
- Rugged body which protects electronics against moisture & vibration.
- Effective resistance towards common surges.
- Reliable performance even in humid environments.

PRODUCT DETAILS

LIGHTING PERFORMANCE						
Efficacy 130	130 lm/W					
Power 75	75 W 100 W 130 W 150 W					
Lumen Output 975	9750 lm 13000 lm 16900 lm 19500 lm					
CCT 400	4000 K, 4500 K, 5000 K, 5700 K					
CRI 80-	80+					
Voltage AC	AC 100-277 V 50/60 Hz					
Beam Angle 110	110°					
Power factor ≥ 0	≥ 0.90					
Dimming Yes	S					

ENVIRONMENT & LIFESPAN			
Operating Temperature	-13° F to +104° F		
IP Rating	IP65		
Operating Hours	Over 100,000 hours lifetime at L70		
Warranty	10 Years		

CONSTRUCTION	
Housing	Aluminum + Polycarbonate
Base / Power Supply	Hard Wired
Finish	White

APPLICATIONS

Commercial Spaces, Parking lots, Gas Stations, Other Industrial Spaces

QUALIFICATIONS & WARRANTY








WEIGHT AND DIMENSIONS

Weight 09 lbs

Wattage	A(in)	B(in)	C(in)
75 W - 150 W	15.11	15.11	2.75



ORDERING INFORMATION

MODEL		POWER		ССТ
IK-CPSL	-	75 W	-	4000 K
		100W 130W 150W		4500K 5000 K 5700 K



Product Specification Sheet | Industrial Lighting

PACKAGING		
Quantity Per Box	1	
Box Dimensions	16" x 16" x 5"	
Box Weight	11 lbs	

ACCESSORIES / REPLACEMENT PARTS

PENDANT MOUNT BRACKET: GAS STATION CANOPY
SURFACE MOUNT SCREWS: GAS STATION CANOPY
REPLACEMENT DRIVER 75W, 100W, 130W, 150W
EMERGENCY BATTERY BACK UP DRIVER 10W/90MIN