

Ortus Recessed Retrofit Downlight 4"

FEATURES

- Offers up to 80% energy saving in comparison to incandescent/halogen bulbs.
- Designed to fit most 4" cans.
- Switches on instantly.
- Suitable for damp locations.
- Compatible with most dimmers down to 10%.
- Requires no special tools for installation.

PRODUCT DETAILS

LIGHTING PERFORMANCE

| | | |
|--------------|-----------------------------------|--------|
| Efficacy | 75 lm/W | |
| Power | 08 W | 10 W |
| Lumen Output | 600 lm | 750 lm |
| CCT | 2700 K / 3000 K / 4000 K / 5000 K | |
| CRI | 90+ | |
| Voltage | 120 V or 277 V, 50 / 60 Hz | |
| Beam Angle | 120° | |
| Power factor | ≥ 0.90 | |
| Dimming | Triac Dimmable | |

ENVIRONMENT & LIFESPAN

| | |
|-----------------------|------------------|
| Operating Temperature | -4° F to +113° F |
| IP Rating | IP40 |
| Operating Hours | 50,000 hours |
| Warranty | 5 Years |

ORDERING INFORMATION

| MODEL | Wattage | CCT |
|--------------|--------------|---|
| IK-DLR4-ECON | 0008 0010 | 27 27 - 2700 K 50 - 5000 K 30 - 3000 K 40 - 4000 K |

CONSTRUCTION

| | |
|---------------------|---------------------|
| Housing | Aluminum |
| Base / Power Supply | E26 / GU24 |
| Finish | Architectural White |


APPLICATIONS

Ideal for retrofitting inefficient fixtures in residential ceilings.

QUALIFICATIONS & WARRANTY



DIMENSIONS



| Wattage | A(in) | B(in) | C(in) |
|------------|-------|-------|-------|
| 8 W - 10 W | 5.08 | 2.88 | 1.2 |

INSTALLATION

1. Cut the installation hole.
2. Connect the input plug to the socket outlet.
3. Place the LED driver and LED downlight into the ceiling.
4. Ensure all the clearance values are maintained after installation for the LED downlight, LED driver, insulation and any structural members. (see Figure 4, 5 and Clearance Information section)

