



Paxon Retrofit Low Bay Lamp

FEATURES

- Perfect replacement for HID's upto 175 W.
- Exceptional efficacy and quality of light output.
- Savings of up to 75% over conventional fluorescent fixtures.
- Eliminates "hot spot" with its wide and even distribution of light.
- No use of Mercury.
- Ideal for operation in humid environment.

PRODUCT DETAILS

LIGHTING PERFORMANCE


Efficacy	110 lm/W	
Power	40 W	60 W
Lumen Output	4400 lm	6600 lm
CCT	4000 K, 4500 K, 5000 K, 5700 K	
CRI	80+	
Voltage	AC 100-277 V 50/60 Hz	
Beam Angle	360°	
Power factor	≥ 0.90	
Dimming	No	
Diffuser Type	Frosted/ Clear	

ENVIRONMENT & LIFESPAN

Operating Temperature	-27° F to +130° F
IP Rating	IP65
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

DIMENSIONS

Wattage	A(in)	B(in)
40 W	6.88	8.07
60 W	7.75	7.75



CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	Hard Wired (Screw-in to existing fixture)
Finish	White

APPLICATIONS

Outdoor Lighting, Parking Garage, Fuel Pumps, Workshops, etc.

QUALIFICATIONS & WARRANTY



ORDERING INFORMATION

MODEL	POWER	CCT
IK-LBKT	- 0040 0060	- 40-E(X)39 40- 4000K 45- 4500K 50- 5000K 57- 5700K



PACKAGING

Quantity Per Box	1
Box Dimensions	-----
Box Weight	-----

OPTOMETRIC DATA

40 W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



60 W

