



RAYDENT

STADIUM FLOOD LIGHT



Not all product variations listed on this page are DLC qualified. Visit <https://www.designlights.org/qpl> to confirm qualification.

IKIO's Raydent Flood Light features visor technology for precise light control. With superior efficacy and multi-faceted optics, it delivers low-glare, powerful illumination for large stadiums, playfields, and sports arenas. Its rugged die-cast design ensures durability in harsh weather, while the efficient heat sink and 3.04ft² EPA provide long-term stability for the lighting system. This combination makes Raydent the ideal choice for venues demanding reliable and high-performance lighting.

Applications: Stadiums and Sports Venues, Outdoor Advertising, Gymnasiums, Plazas, Airports, Courtyards, Public Areas

FEATURES

- **Premium multifaceted** polycarbonate lens maximizes light output while ensuring even distribution.
- With an **IP65 rating and EPA of up to 3.04ft²**, the fixture is built to deliver stable performance in harsh outdoor environments.
- **1-10V dimming control** offers flexible light output adjustments, while instant start technology eliminates flickering and humming.
- **Visor and laser** pointer options available.
- **Compatible with DMX control**, allowing dynamic behaviors such as color-changing, grouping, scheduling, and remote operation.
- Equipped with **6kV + 10kV** surge protection for reliability during fluctuations.
- **Engineered for easy installation**, this fixture simplifies the transition to LED, making it ideal for quick, cost-effective upgrades.

Note: Warranty and Qualifications can vary per item, see technical data sheets (TDS) for specific information. • Not all product variations listed are DLC® qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PRODUCT ORDERING DETAILS

RAYDENT STADIUM FLOOD LIGHT

POWER	SKU NUMBER	DESCRIPTION	DLC	EFFICACY	SPEC SHEET
753.7W	662187501598	RAYDENT SFL: 753.7W / 118431LM / 4000K / 120-277V / BLACK	•	157.13lm/W	View / Download
752.8W	662187487618	RAYDENT SFL: 752.8W / 118487LM / 5000K / 120-277V / BLACK	•	157.4lm/W	View / Download
751.8W	662187501604	RAYDENT SFL: 751.8W / 118543LM / 5700K / 120-277V / BLACK	•	157.68lm/W	View / Download

ACCESSORIES

SOLD SEPARATELY

SKU NUMBER	PRODUCT CODE	DESCRIPTION	SPEC SHEET
662187487632	IK-ACC-SP08-FLOODMOUNT	FLOOD MOUNTING BRACKET	View / Download
662187487960	IK-ACC-SP08-SLIPFITTER	SLIP FITTER MOUNTING BRACKET	View / Download
662187487649	IK-ACC-SP08-SHIELD	SHIELD	View / Download
662187482231	IK-PHC-3PIN-AC100-277V	PHOTOCELL (3 PIN) AC100-277V	View / Download
662187540160	IK-PHC-5PIN-AC100-277V	PHOTOCELL (5 PIN) AC100-277V	View / Download
662187540177	IK-PHC-7PIN-AC100-277V	PHOTOCELL (7 PIN) AC100-277V	View / Download
662187483634	IK-PHC-3PIN-SOCKET-0-480V	PHOTOCELL (3 PIN) SOCKET AC 0-480V	View / Download
662187483641	IK-PHC-5PIN-SOCKET-0-480V	PHOTOCELL (5 PIN) SOCKET AC 0-480V	View / Download
662187487755	IK-PHC-7PIN-SOCKET-0-480V	PHOTOCELL (7 PIN) SOCKET AC 0-480V	View / Download
662187486543	IK-ACC-SPD-10KV-(100-277V)	SURGE PROTECTION 10KV	View / Download
662187487625	IK-ACC-SPD-20KV-(100-277V)	SURGE PROTECTION 20KV	View / Download

**Choice of one accessory: Mounting Bracket (Slip Fitter or Flood Mount—either one) is included with the order.
Contact your IKIO sales representative to buy replacement/additional Mounting Bracket.*

