

Product Specification Sheet

NOTES:
PROJECT NAME :
CATALOG NO.:
FIXTURE SCHEDULE :



Rollo 2 Wall Light

FEATURES

- Superior efficacy over traditional light fixtures.
- · Rated for use in wet locations.
- Acrylic Diffuser for effective light distribution.
- Comes with a 120V Triac Dimmable Driver for enhanced light control.
- Finished in Black / Oil-Rubbed Bronze for better aesthetics.
- Steel housing for enhanced protection against weathering.
- Long-lasting LED Light Engine Driver for durability.
- 80+ CRI light for crisp colors.

PRODUCT DETAILS

LIGHTING PERFORMANCE							
Efficacy	70 lm/W						
Power	06 W	09 W	12 W				
Lumen Output	420 lm 630 lm 840 lm						
ССТ	3000 K, 4000 K, 5000 K						
CRI	80+						
Voltage	120 V-277 V, 50 Hz / 60 Hz						
Power factor	≥ 0.90						
Dimming	Yes						
Dimming	Yes						

ENVIRONMENT & LIFESPAN						
IP Rating	IP20					
Operating Hours	50,000 hours					
Warranty	5 Years					

CONSTRUCTION						
Finish	Black, Oil Rubbed Bronze					
Material	Steel					
Lens	Acrylic					

APPLICATIONS

Ideal for Entrances, Entryways, Porches or other Outdoor Heavy-duty applications.

QUALIFICATIONS & WARRANTY







DIMENSIONS

Wattage	A(in)	B(in)
06 W / 00 W / 12 W	10	10



ORDERING INFORMATION

MODEL		WATTAGE		CRI & CCT		DRIVER		FINISH		DIFFUSER
IK-OWL2-08P	-	06WD	-	80C3K	-	120VDY	-	ВК	-	С
	'	06WD		80C3K		120VDY		BK-Black		C- Clear
		09WD		80C4K				ORB-Oil Rubbed Bronz	ze	F - Frosted
		12WD		80C5K						W - White