I LE	D LIGHTING	
Product	Specification	Sheet

NOTES:
PROJECT NAME :
CATALOG NO. :
FIXTURE SCHEDULE :



Slitz 2 Up - Down Light

FEATURES

- Superior efficacy over traditional light fixtures.
- Rated for use in wet locations.
- Clear Glass Diffuser for effective light distribution.
- Finished in Black / Grey / White for better aesthetics.
- · Aluminum housing for enhanced protection against weathering.
- · Long-lasting LED Light Engine Driver for durability.
- 80+ CRI light for crisp colors.

PRODUCT DETAILS

LIGHTING PERFORMANCE						
Efficacy	90 lm/W					
Power	12 W					
Lumen Output	1080 lm					
ССТ	3000 K, 4000 K, 5000 K					
CRI	80+					
Voltage	120 V-277 V, 50 Hz / 60 Hz					
Power factor	≥ 0.90					
Dimming	No					

ENVIRONMENT & LIFESPAN						
IP Rating	IP20					
Operating Hours	50,000 hours					
Warranty	5 Years					

CONSTRUCTION				
Finish	Black, Grey, White			
Material	Aluminum			
Lens	Glass			

APPLICATIONS

Ideal for Entrances, Entryways, Porches or other Outdoor Heavy-duty applications.

QUALIFICATIONS & WARRANTY







DIMENSIONS

Wattage	A(in)	B(in)	
12 \//	0_1/8	4-1/2	



ORDERING INFORMATION

MODEL		WATTAGE		CRI & CCT	DRIVER		FINISH	
IK-OUD1-12G] -	12WS] -	80C3K	 120VDN	-	ВК	
	•	12WS	_	80C3K	 120VDN		BK- Black	
				80C4K			GR - Grey	
				80C5K			WH- White	