



T5 Tube - Type B

FEATURES

- Exceptional lighting efficacy, with low energy and maintenance costs.
- Double-ended power.
- Great efficacy and uniform light output.
- A direct replacement for existing T5 fluorescent lighting systems.
- Unique design with a perfectly uniform visual appearance.
- Works with line voltage.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	150 lm/W
Power	24 W
Lumen Output	3600 lm
CCT	2700 K, 5000 K
CRI	80+
Voltage	AC 100-277 V 50/60 Hz
Beam Angle	360°
Power factor	≥ 0.90
Dimming	No

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +113° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Polycarbonate and Aluminum
Base / Power Supply	Hard Wired
Diffuser	Clear / Frosted

APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
24 W	48	0.19	0.90



ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT
IK-T504	0024	DN	2630B 5000B

PACKAGING

Quantity Per Box	25
Box Dimensions	-----
Box Weight	-----

OPTOMETRIC DATA

24W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

