



T5 Tube - Type B

FEATURES

- Exceptional lighting efficacy, with low energy and maintenance costs.
- Great efficacy and uniform light output.
- A direct replacement for existing T5 fluorescent lighting systems.
- Unique design with a perfectly uniform visual appearance.
- Works with line voltage.

PRODUCT DETAILS

LIGHTING PERFORMANCE

| | | |
|--------------|-----------------------|---------|
| Efficacy | 160 lm/W | |
| Power | 15 W | 18 W |
| Lumen Output | 2400 lm | 2880 lm |
| CCT | 2700 K, 5000 K | |
| CRI | 80+ | |
| Voltage | AC 100-277 V 50/60 Hz | |
| Beam Angle | 360° | |
| Power factor | ≥ 0.90 | |
| Dimming | No | |

ENVIRONMENT & LIFESPAN

| | |
|-----------------------|-----------------------------------|
| Operating Temperature | -13° F to +113° F |
| IP Rating | IP20 |
| Operating Hours | Over 50,000 hours lifetime at L70 |
| Warranty | 5 Years |

CONSTRUCTION

| | |
|---------------------|----------------------------|
| Housing | Polycarbonate and Aluminum |
| Base / Power Supply | Hard Wired |
| Diffuser | Clear / Frosted |

APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

QUALIFICATIONS & WARRANTY



DIMENSIONS

| Wattage | A(in) | B(in) | C(in) |
|-------------|-------|-------|-------|
| 15 W - 18 W | 48.00 | 0.19 | 0.90 |



ORDERING INFORMATION

| MODEL | POWER | DIMMING | CCT |
|---------|--------------|---------|----------------|
| IK-T504 | 0015 0018 | DN | 2630B 5000B |

PACKAGING

| | |
|------------------|-------|
| Quantity Per Box | 25 |
| Box Dimensions | ----- |
| Box Weight | ----- |

OPTOMETRIC DATA

18W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

