

## T5 Tube - Type B

### FEATURES

- Exceptional lighting efficacy, with low energy and maintenance costs.
- Great efficacy and uniform light output.
- A direct replacement for existing T5 fluorescent lighting systems.
- Unique design with a perfectly uniform visual appearance.
- Works with line voltage.



### PRODUCT DETAILS

#### LIGHTING PERFORMANCE

<b>Efficacy</b>	150 lm/W
<b>Power</b>	24 W
<b>Lumen Output</b>	3600 lm
<b>CCT</b>	2700 K, 5000 K
<b>CRI</b>	80+
<b>Voltage</b>	AC 100-277 V 50/60 Hz
<b>Beam Angle</b>	360°
<b>Power factor</b>	≥ 0.90
<b>Dimming</b>	No

#### ENVIRONMENT & LIFESPAN

<b>Operating Temperature</b>	-13° F to +113° F
<b>IP Rating</b>	IP20
<b>Operating Hours</b>	Over 50,000 hours lifetime at L70
<b>Warranty</b>	5 Years

#### CONSTRUCTION

<b>Housing</b>	Polycarbonate and Aluminum
<b>Base / Power Supply</b>	Hard Wired
<b>Diffuser</b>	Clear / Frosted

#### APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

#### QUALIFICATIONS & WARRANTY



### DIMENSIONS

Wattage	A(in)	B(in)	C(in)
24 W	48	0.19	0.90



### ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT
IK-T504	0024	DN	2630B 5000B

**PACKAGING**

Quantity Per Box 25


Box Dimensions -----

Box Weight -----

**OPTOMETRIC DATA**

24W

**LUMINOUS INTENSITY DISTRIBUTION DIAGRAM**



Flux out: 2098 lm

