



T5 Tube - Type C

FEATURES

- Exceptional lighting with low energy and maintenance costs; up to 75% savings over conventional fixtures.
- Compatible with shunted and non-shunted tombstones.
- Ideal for operation in low temperatures.
- Works with external driver, with a surge protection of up to 5 kV.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	125 lm/W		
Power	18 W	25 W	30 W
Lumen Output	2250 lm	3125 lm	3750 lm
CCT	3000 K, 3500 K, 4000 K, 5000 K		
CRI	80+		
Voltage	AC 100-277 V 50/60 Hz (With External Driver Use Only)		
Beam Angle	360°		
Power factor	≥ 0.90		
Dimming	No		

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +113° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	Hard Wired (With IKIO External Driver)
Diffuser	Clear / Frosted

APPLICATIONS


Ideal for up-gradation of existing linear fluorescent fixtures or retrofitting surface mount.

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
18 W - 30 W	48	0.19	0.90



ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT	TYPE AND NO. OF LAMPS/ FIXTURE
IK-T504	0018 0025 0030	DN DY	30 30- 3000K 35- 3500K 40- 4000K 50- 5000K	C-J C-2-J C-3-J C-4-J

PACKAGING



Quantity Per Box	30
Box Dimensions	-----
Box Weight	-----

ACCESSORIES / REPLACEMENT PARTS



36W TYPE C DRIVER FOR (2) LED 18WT8 TUBES/120-277V/NON-DIMMABLE/ DIMMABLE
50W TYPE C DRIVER FOR (2) LED 25WT8 TUBES/120-277V/NON-DIMMABLE/ DIMMABLE
60W TYPE C DRIVER FOR (3) LED 18WT8 TUBES OR (2) 30WT8 TUBES 120-277V/NON-DIMMABLE/ DIMMABLE
80W TYPE C DRIVER FOR (3) LED 25WT8 TUBES 120-277V/NON-DIMMABLE/ DIMMABLE

OPTOMETRIC DATA

18 W



25 W



30 W

