



T8 Tube - Type B (8 ft)

FEATURES

- Can be run directly off main with no major rewiring.
- Exceptional efficacy and light output with a wide beam.
- Low energy consumption and maintenance cost.
- Does not need a ballast to work.
- Comes with an in-built universal line voltage driver.
- No flickering.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	145 lm/W
Power	40 W
Lumen Output	5800 lm
CCT	3000 K, 3500 K, 4000 K, 5000 K
CRI	80+
Voltage	AC 100-277 V 50/60 Hz
Beam Angle	180°
Power factor	≥ 0.90
Dimming	Optional

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +113° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	FA08 / G13 / R14D / Hard Wired
Diffuser	Clear / Frosted

APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
40 W	96	0.50	1.15



ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT
IK-T808	0040	DN DY	30B-J 30- 3000K 35- 3500K 40- 4000K 50- 5000K

PACKAGING

Quantity Per Box 20

Box Dimensions -----

Box Weight -----

OPTOMETRIC DATA

40 W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

