



T8 Tube - Type B (4 ft)

FEATURES

- Exceptional efficacy and light output with a wide beam.
- Low energy consumption and maintenance cost.
- Does not need a ballast to work.
- Comes with an in-built universal line voltage driver.
- No flickering.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	140 lm/W	120 lm/W	140 lm/W
Power	13 W	18 W	22 W
Lumen Output	1820 lm	2160 lm	3080 lm
CCT	3000 K, 3500 K, 4000 K, 5000 K		
CRI	80+		
Voltage	AC 100-277 V 50/60 Hz		
Beam Angle	180°		
Power factor	≥ 0.90		
Dimming	No		

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +113° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	G13 / Direct Wire
Diffuser	Clear / Frosted

APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
13 W / 18 W / 22 W	48	0.50	1.15



ORDERING INFORMATION



MODEL	POWER	DIMMING	CCT
IK-T804	0013 0018 0022	DN	40B-J 30- 3000K 35- 3500K 40- 4000K 50- 5000K

PACKAGING



Quantity Per Box	30
Box Dimensions	-----
Box Weight	-----

OPTOMETRIC DATA

13 W



18 W



22 W

