



T8 Tube - Type C (4 ft)

FEATURES

- Exceptional lighting with low energy and maintenance costs; up to 75% savings over conventional fixtures.
- Compatible with shunted and non-shunted tombstones.
- Ideal for operation in low temperatures.
- Works with external driver, with a surge protection of up to 5 kv.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	130 lm/W	140 lm/W	140 lm/W
Power	12 W	15 W	18 W
Lumen Output	1560 lm	2100 lm	2520 lm
CCT	3000 K, 3500 K, 4000 K, 5000 K		
CRI	80+		
Voltage	AC 100-277 V 50/60 Hz		
Beam Angle	180°		
Power factor	≥ 0.90		
Dimming	Optional		

ENVIRONMENT & LIFESPAN

Operating Temperature	-13° F to +113° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years

CONSTRUCTION

Housing	Aluminum + Polycarbonate
Base / Power Supply	For Use with External Driver Only
Diffuser	Clear / Frosted

APPLICATIONS


Commercial Spaces, Residential Area and Office Area.

QUALIFICATIONS & WARRANTY



DIMENSIONS

Wattage	A(in)	B(in)	C(in)
12 W / 15 W / 18 W	48	0.50	1.15



ORDERING INFORMATION

MODEL	POWER	DIMMING	CCT
IK-T804	EX0012	DN	30C-J
	EX0015	DY	30- 3000K
	EX0018		35- 3500K
			40- 4000K
			50- 5000K

PACKAGING

Quantity Per Box	30
Box Dimensions	-----
Box Weight	-----



ACCESSORIES / REPLACEMENT PARTS

25W TYPE C DRIVER FOR (2) LED 12WT8 TUBES/120-277V/NON DIMMABLE/ DIMMABLE
30W TYPE C DRIVER FOR (2) LED 15WT8 TUBES/120-277V/NON DIMMABLE/ DIMMABLE
60W TYPE C DRIVER FOR (4) LED 15WT8 TUBES OR (3) 18WT8 TUBES/120-277V/NON DIMMABLE/ DIMMABLE
EMERGENCY PACK FOR LED FIXTURE 10W/90 MIN/SPLIT TYPE/L
EMERGENCY PACK FOR LED FIXTURE 15W/90 MIN/SPLIT TYPE/L

OPTOMETRIC DATA



12 W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



15 W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



18 W

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

