



Taz CCT Tunable Downlight (Round) 4 inch

FEATURES

- Has variable CCT options which can be controlled by its switch.
- Offers 80% energy saving in comparison to incandescent/halogen bulbs.
- Fits most 4 inch cans.
- Switches on instantly.
- Compatible with most dimmers, down to a minimum of 5%.
- Requires no special tools for its installation.

PRODUCT DETAILS

LIGHTING PERFORMANCE

Efficacy	75 lm/W
Power	8 W
Lumen Output	600 lm
CCT	CCT Tunable 3000 K, 4000 K, and 5000 K
CRI	90+
Voltage	120 V, 50 / 60 Hz
Beam Angle	120°
Power factor	≥ 0.90
Dimming	Triac Dimmable

ENVIRONMENT & LIFESPAN

Operating Temperature	-4° F to +113° F
IP Rating	IP40
Operating Hours	50,000 hours
Warranty	5 Years

ORDERING INFORMATION

MODEL	Wattage
IK-DL04-MCCT	- 0008 -XX

CONSTRUCTION

Housing	Aluminum
Base / Power Supply	E26 / GU24
Finish	Architectural White


APPLICATIONS

Ideal for retrofitting inefficient fixtures in residential ceilings.

QUALIFICATIONS & WARRANTY



DIMENSIONS



Wattage	A(in)	B(in)	C(in)
8 W	4.00	2.78	0.96

INSTALLATION

1. Cut the installation hole.
2. Connect the input plug to the socket outlet.
3. Place the LED driver and LED downlight into the ceiling.

4. Ensure all the clearance values are maintained after installation for the LED downlight, LED driver, insulation and any structural members. (see Figure 4, 5 and Clearance Information section)

