

Product Specification Sheet | Commercial Lighting

NOTES:	
PROJECT NAME :	
CATALOG NO. :	
FIXTURE SCHEDULE :	



Toucan Architectural Troffer 2' x 2'

FEATURES

- · Soft, smooth and uniform light output.
- Suitable for a wide range of applications due to it's low profile.
- Up to 30% reduction in energy consumption over traditional linear fluorescent fixtures.
- Metal surfaces are painted pre-fabrication with high gloss baked white matte powder paint, for better and long lasting finish.

PRODUCT DETAILS

LIGHTING PERFORMANCE			
Efficacy	130 lm/W		
Power	25 W	36 W	
Lumen Output	3250 lm	4680 lm	
ССТ	3000 K, 3500 K, 4000 K, 5000 K		
CRI	80+		
Voltage	AC 100-277 V 50/60 Hz		
Beam Angle	120°		
Power factor	≥ 0.90		
Dimming	Yes		

ENVIRONMENT & LIFESPAN

Operating Temperature	-04° F to +122° F
IP Rating	IP20
Operating Hours	Over 50,000 hours lifetime at L70
Warranty	5 Years / 10 Years (Optional)

CONSTRUCTION

Housing	Aluminum / Metal sheet		
Base / Power Supply	Hard Wired		
Finish	White		

APPLICATIONS

Ideal for large warehouses, retail applications, commercial buildings and work areas.

QUALIFICATIONS & WARRANTY











DIMENSIONS

Wattage	A(in)	B(in)	C(in)
25 W - 36 W	24	24	3.25





ORDERING INFORMATION

MODEL		POWER		ССТ	
IK-AT22	-	0025	-	35-J	
		0036		30-3000K	
				35-3500K	
				40-4000K	
				50-5000K	

Email: info@ikioledlighting.com Website: www.ikioledlighting.com Phone: +(1) 844-533-4546



Product Speci~cation Sheet | Commercial Lighting

PACKAGING

Quantity Per Box	1
Box Dimensions	
Box Weight	

ACCESSORIES / REPLACEMENT PARTS

EMERGENCY PACK FOR LED FIXTURE 10 W / 90 MIN / SPLIT TYPE / L

EMERGENCY PACK FOR LED FIXTURE 15 W / 90 MIN / SPLIT TYPE/ L

SMART OCCUPANCY SENSOR WITH DAYLIGHT HARVESTING CAPABILITY

REPLACEMENT REMOTE FOR SMART OCCUPANCY SENSOR

REPLACEMENT DRIVER

OPTOMETRIC DATA



